

# twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

## Nivel Laser TD-12 Boka

BK-TD12

[www.twilight.mx](http://www.twilight.mx)



/ twilightSadecv




/ twilightSadecv



/ twilightSadecv

# twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

|  |   |       |  |  |  |                   |  |                                    |                         |                    |                               |
|--|---|-------|--|--|--|-------------------|--|------------------------------------|-------------------------|--------------------|-------------------------------|
| TD-12                                    |  | Green | <ol style="list-style-type: none"> <li>1. Soft case</li> <li>2. English User manual</li> <li>3. Adjustable Base</li> <li>4. Magnetic Bracket</li> <li>5. 2*18650mh batteries</li> <li>6. Charger</li> <li>7. Adapter</li> <li>8. Remote control</li> </ol> | <ol style="list-style-type: none"> <li>1. High power green laser diode</li> <li>2. Rubber-covered shell</li> <li>3. 360° full lines</li> <li>4. One 360° floor laser window</li> <li>5. Battery level indicator</li> </ol> | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="padding: 2px;">Wavelength: 532nm</td> </tr> <tr> <td style="padding: 2px;">Horizontal/vertical accuracy: ± 1.5mm/5m</td> </tr> <tr> <td style="padding: 2px;">Compensator performance range: ±3°</td> </tr> <tr> <td style="padding: 2px;">Waterproof grade: IP-54</td> </tr> <tr> <td style="padding: 2px;">Working range: 20m</td> </tr> <tr> <td style="padding: 2px;">Working temperature: -10-40°C</td> </tr> </table> | Wavelength: 532nm | Horizontal/vertical accuracy: ± 1.5mm/5m | Compensator performance range: ±3° | Waterproof grade: IP-54 | Working range: 20m | Working temperature: -10-40°C |
| Wavelength: 532nm                        |   |       |  |  |  |                   |  |                                    |                         |                    |                               |
| Horizontal/vertical accuracy: ± 1.5mm/5m |   |       |  |  |  |                   |  |                                    |                         |                    |                               |
| Compensator performance range: ±3°       |   |       |  |  |  |                   |  |                                    |                         |                    |                               |
| Waterproof grade: IP-54                  |   |       |  |  |  |                   |  |                                    |                         |                    |                               |
| Working range: 20m                       |   |       |  |  |  |                   |  |                                    |                         |                    |                               |
| Working temperature: -10-40°C            |   |       |  |  |  |                   |  |                                    |                         |                    |                               |

# twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:  
01 800 087 43 75

E-mail:  
[ventas@twilight.mx](mailto:ventas@twilight.mx)

[www.twilight.mx](http://www.twilight.mx)



/ [twightsadecv](https://www.facebook.com/twightsadecv)



/ [twightsadecv](https://twitter.com/twightsadecv)



/ [twightsadecv](https://www.youtube.com/twightsadecv)