

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Medidor de Humedad en Concreto DH-TCHECK/CP

www.twilight.mx

 / [twilightsadecv](#)

 / [twilightsadecv](#)

 / [twilightsadecv](#)



PRODUCT FEATURES

- Bright, clear digital display.
- Pin Mode:
 - 5%-60% wood scale.
 - Corrects for 69 individual wood species and temperature (°F and °C).
 - 0.1% – 6% drywall scale.
 - 0–100 numerical reference scale for non-wood building materials.
 - Built-in connector accepts any Delmhorst electrode.
- Scan Mode: 0–300 numerical reference scale.
- Thermo-hygrometer with RH sensor:
 - Temperature Range: 0°F - 255°F (-18°C - 124°C).
 - Relative Humidity Range: 0%–100%.
 - Dew Point Range: -40°F - 176°F (-40°C - 80°C).
 - GPP Range: 0.1 - 3820 GPP (Grains Per Pound).
 - Sensor can be used for in-situ concrete testing following the ASTM F2170 standard.
- Store up to 1400 readings with date and time stamp.
- View stored readings on screen.
- Organize readings by job for easy reference.
- Optional software lets you download readings to your computer and generate Excel reports.
- Size: 8 ½” x 3 3/8” x 1 ¾”.
- Weight: 11 oz.
- Rugged construction ensures years of reliable use.
- Sturdy plastic carrying case.
- 9V battery.
- 1-year warranty.

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx



/ [twightsadecv](https://www.facebook.com/twightsadecv)



/ [twightsadecv](https://twitter.com/twightsadecv)



/ [twightsadecv](https://www.youtube.com/twightsadecv)