

# twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

## Medidor de Rotación de Fase Mecanico, Hioki HK-312601

[www.twilight.mx](http://www.twilight.mx)

 / [twilightsadecv](https://www.facebook.com/twilightsadecv)

 / [twilightsadecv](https://twitter.com/twilightsadecv)

 / [twilightsadecv](https://www.youtube.com/twilightsadecv)

### Classic Phase Rotation Detector

The Hioki 3126-10 is a phase rotation detector with 110V to 480V detection range.



Not CE Marked

#### ■ Basic specifications

Voltage range	110 to 480 V AC (40 Hz to 70 Hz)
Time limits	30 minutes /220 V AC, 4 minutes /480 V AC
Connection cable length	1.2 m (R: red, S: white, T: blue), with clip and fuse holder (700 V/ 0.5 A fuse)
Dimensions and mass	70 mm (2.76 in) W × 96 mm (3.78 in) H × 54 mm (2.13 in) D, 280 g (9.9 oz)
Accessories	Carrying case ×1, Instruction manual ×1, Spare fuse ×1

# twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:  
01 800 087 43 75

E-mail:  
[ventas@twilight.mx](mailto:ventas@twilight.mx)

[www.twilight.mx](http://www.twilight.mx)



/ [twightsadecv](https://www.facebook.com/twightsadecv)



/ [twightsadecv](https://twitter.com/twightsadecv)



/ [twightsadecv](https://www.youtube.com/twightsadecv)