

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Torquimetro para Herramientas Neumáticas 200 N-m IM-DI1M200

www.twilight.mx

 / [twilightsadecv](https://www.facebook.com/twilightsadecv)

 / [twilightsadecv](https://twitter.com/twilightsadecv)

 / [twilightsadecv](https://www.youtube.com/twilightsadecv)



DI-1M Ranges

Accuracy $\pm 0.5\%$ F.S., ± 1 LSD

[More Ranges](#) ►

<u>Model</u>	<u>Capacity (Resolution)</u>				
	lbf-in	lbf-ft	kgf-cm	kgf-m	N-m
DI-1M-50	3.0~440.0	-	3.0~500.0	-	30~5000 (N-cm)
DI-1M-200A	30~1740	-	30~2000	-	3.0~200.0
DI-1M-200	-	3.0~145.0	-	0.30~20.00	3.0~200.0
DI-1M-500	-	3.0~362.0	-	0.30~50.00	3.0~500.0
DI-1M-HP250	-	3.0~180.0	-	3.0~25.0	30.0~250.0

SJ Spring Adapter Specifications

Model	Capacity	Drive	Screw	for Model
SJ-200	200 lbf-in	3/8"	3/8-16	DI-1M-50
SJ-300	300 lbf-in	3/8"	1/2-13	DI-1M-50
SJ-500	500 lbf-in	1/2"	1/2-13	DI-1M-200
SJ-1500	1500 lbf-in	1/2"	3/4-10	DI-1M-200
SJ-2000	2000 lbf-in	3/4"	3/4-10	DI-1M-500

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx



/ [twightsadecv](https://www.facebook.com/twightsadecv)



/ [twightsadecv](https://twitter.com/twightsadecv)



/ [twightsadecv](https://www.youtube.com/twightsadecv)