

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Negatoscopio Portatil LED Uso Industrial Densitometro LCNDT LC-FV2009T

www.twilight.mx

LC NDT FV-2009-T LED Film Viewer with built-in Densitometer



Upgraded Features:

- ☐ **Increased Intensity:** $120,000 \text{ Cd/m}^2 = 4.1D$
- ☐ **Stainless Steel Hardware** – More Durable – Resistant to Corrosion
- ☐ High Uniformity across viewing window
- ☐ **Wall-mount-brackets** – standard

The FV-2009-T combines the capabilities of the popular FV-2009 LED Film Viewer with the DT-200 Densitometer in a portable and convenient package.

Film Viewer

- ☐ High Luminance: $\geq 120,000 \text{ Cd/m}^2$
- ☐ Maximum Density: 4.1 D
- ☐ Viewer Window: 2.5" x 8" (60mm x 200mm)
- ☐ Diffusion Factor: $g \geq 0.95$
- ☐ Uniformity: $g \geq 0.95$
- ☐ Surface Temperature Rise: $\leq 59^\circ\text{F}$ (15°C)
- ☐ Dimensions: 17.9" x 5.5" x 2.6" (455mm x 140mm x 65mm)
- ☐ Power: 85 – 264 VAC / 47 – 63 Hz
- ☐ Weight: 5.5 lbs. (2.5 kg)
- ☐ Warranty: 5 years parts, 1 year labor

Densitometer

- ☐ High Accuracy: $\pm 0.03D$
- ☐ Density: 0 to 5 D
- ☐ Range: 650 Cd/m^2 and $320,000 \text{ Cd/m}^2$
- ☐ Resolution: 0.01 D
- ☐ Probe: Temperature compensated
- ☐ 3mm Aperature
- ☐ Display: 4 Digit LCD
- ☐ 10 Point Calibration
- ☐ User calibration mode
- ☐ Warranty: 5 years parts, 1 year labor

FV-2009-T Package Includes:

- ☐ Film Viewer with Built-In Densitometer
- ☐ Densitometer Probe
- ☐ Foot Pedal
- ☐ Carrying Case
- ☐ Mask: 2.4" x 6" (60mm x 150mm)
- ☐ Mask: 1.8" x 6" (45mm x 150mm)
- ☐ Instruction Manual
- ☐ Certification Report
- ☐ Warranty Card

Shipping:

- ☐ Weight: 10 lbs. (4.5kg)
- ☐ Dimensions: 20" x 8" x 9" (50.8cm x 20cm x 22.5cm)

Warranty
5 Years Parts, 1 Year Labor





INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx



/ twilightsadecv



/ twilightsadecv



/ twilightsadecv