

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Refractómetro digital automático RX-5000i

RX-5000i

www.twilight.mx

 / [twightsadecv](https://www.facebook.com/twightsadecv)

 / [twightsadecv](https://twitter.com/twightsadecv)

 / [twightsadecv](https://www.youtube.com/twightsadecv)



The most accurate refractometer in the world is now even more stylish, smart, and functional, featuring intuitive touch screen technology, the new RX-i series makes navigation and selection a breeze. The RX-5000i measures with the same accuracy level as the RX-5000α ±0.03% Brix and ±0.00004 nD. The RX-i series come with newly added functions, such as USB flash drive and self-diagnosis capability. This product comes standard with a two (2) year limited warranty against manufacturer's defects from the date of the original purchase. The warranty period can be extended to three (3) years if the product is registered with ATAGO. FDA 21 CFR Part 11 Software Included in Standard Delivery.



Specifications	
Model	RX-5000i
Cat.No.	3276
Range	Refractive index (nD) : 1.32420 to 1.58000 Brix : 0.00 to 100.00%
Resolution	Refractive index (nD) : 0.00001 Brix : 0.01% Temperature: 0.01°C
Accuracy	Refractive index (nD) : ±0.00004 Brix : ±0.03%
Temperature control range	5.00 to 75.00°C
Dimensions & Weight	37×26×14cm, 6.6kg
Output	<ul style="list-style-type: none"> • Printer (for ATAGO digital printers) • Computer -USB
Warranty	2 years standard (3 years with product registration) excluding touchscreen
Pre-programmed special scales	Glucose Fructose HFCS-55 HFCS-42 Inverted Sugar Honey moisture Hydrogen peroxide Sodium hydroxide Sodium chloride(w/w) Sodium chloride(w/v) Salinity Ethyl alcohol(w/w) Ethyl alcohol(v/v) Ethylene glycol Propylene glycol Glycerin Urea Urine S.G. Copper sulfate S.G. Vol%FSII (fuel system icing inhibitor) based on ASTM D5006

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx