

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Termómetro Digital de Contacto/Inmersión TE-1300

www.twilight.mx



/ [twilightsadecv](https://www.facebook.com/twilightsadecv)



/ [twilightsadecv](https://twitter.com/twilightsadecv)



/ [twilightsadecv](https://www.youtube.com/twilightsadecv)



Measuring Rang	-50°C ~ 1300°C, -50°F ~ 1999°F
Sensor	K Type Thermocouple
Input	Single Channel / Dual Channel
Resolution	-50°C ~ 199.9°C.....0.1°C -50°F ~ 199.9°F.....0.1°F (Others 1°C/1°F)
Accuracy	-50°C ~ 199.9°C...0.3%rdg + 1°C -50°F ~ 199.9°F...0.3%rdg + 2°F -50°C ~ 1000°C...0.5%rdg + 1°C -50°F ~ 1999°F...0.5%rdg + 2°F 1000°C~ 1300°C...0.75%rdg + 1°C (apply to mainframe only at 23°C± 5°C)
Auxiliary Outputs(for Data Recording)	1mV/°C (°F)...at 0.1°C/0.1°F range 0.1mV/°C (°F)...at 1°C/1°F range
Temperature Coefficient	Less that 0.1 times the applicable accuracy specification per °C (°F)
Input Protection	60V DC or 24 Vrms AC maximum input voltage on any Combination of input Connector
Sampling Rate	2.5 times/sec
Operating Conditions	0°C ~ 50°C (32°F ~ 122°F) 0 ~ 80% R.H.
Power Source	One 9V battery (006P or IEC6F22)
Size	135mm(L)×72mm(W)×31mm(H)
Weight	235g
Accessories	Battery, Instruction, Manual

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx