

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Amperimetro Prova 6600

TE-6600

www.twilight.mx

 / [twilightsadecv](#)

 / [twilightsadecv](#)

 / [twilightsadecv](#)



PROVA-6600 3 Φ Power Clamp

Product Features

- 3*4W, 3*3W, 3* balanced, 1*2W and 1*3W power measurement
- AC+DC true power: 0 ~ 1200KW (AC 600V, DC 800V, ACA/DCA 2000A)
- AC+DC voltage (True RMS): 0 ~ 600V
- AC+DC current (True RMS): 0 ~ 2000A
- AC+DC 1200KW(1*), AC+DC 2000KW (3*)
- Dual display V+Hz, A+Hz, W+PF, KVA+KVAR, V+A
- Phase angle measurement
- Frequency measurement
- 3* RST(L1L2L3) Sequence Indication
- Memory of 4 records
- DCA/DCW auto zero when power clamp powering on
- AC/DC auto detection
- Auto range
- Jaw diameter: 55mm
- Low battery indication

Specification

Application

Download

Electrical Specifications: (23°C±5°C)

AC+DC True Power: (PF 0.2 - 1.0, 3 ϕ 3W, 3 ϕ 4W, 1 ϕ 2W, and 1 ϕ 3W)

Range	Resolution	Accuracy (of reading)	Range
0 - 99.99KW	0.01KW	±2.0%±0.05KW	AC 600V, DC 800V, ACA/DCA 2000A
100 - 999.9KW	0.1KW	±2.0%±0.5KW	
1000-1200KW	1KW	±2.0%±5KW	

KW Autoranging Map: (PF 0.2 - 1.0, 3 ϕ 3W, 3 ϕ 4W, 1 ϕ 2W, and 1 ϕ 3W)

	0V - 200V	200V - 600VAC, 200V - 800VDC
0A - 200A	0.00 - 40.00KW	0.00 - 99.99KW, 100.0 - 160.0KW
200A - 2000A	0.0 - 400.0KW	0.0 - 999.9KW, 1000 - 1600KW

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx



/ [twightsadecv](https://www.facebook.com/twightsadecv)



/ [twightsadecv](https://twitter.com/twightsadecv)



/ [twightsadecv](https://www.youtube.com/twightsadecv)