

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL

Vibrómetro (acc/vel/desplazamiento), salida USB Tenmars TN-ST140D

www.twilight.mx



/ twilightSadecv



/ twilightSadecv



/ twilightSadecv



Specification

Measurement frequency range	Acceleration	10HZ~1KHZ(LO) ; 10HZ~5KHZ(HI)
	Velocity	10HZ~1KHZ
	Displacement	10HZ~1KHZ
Measurement range	Acceleration	0.5~199.9m/s ²
	Velocity	0.5~199.9mm/s
	Displacement	0.005~1.999mm
Function	Acceleration/Velocity	RMS, Peak, Max Hold, Hold
	Displacement	Peak-Peak, Max Hold, Hold
Accuracy	± (5% reading ±5 digits),ref. 79.4/158Hz, 23°C,<80%RH	
Dimension	156x73x35(LxWxH)	
Power supply	1.5V AAA alkaline battery x 6	
AC adapter	AC 100~240V to DC9V/0.5A	
Data stored	9999 records (ST-140D)	

twilight

INSTRUMENTOS DE MEDICIÓN INDUSTRIAL



LLÁMANOS

+52(81) 8115-1400 / +52 (81) 8173-4300

LADA Sin Costo:
01 800 087 43 75

E-mail:
ventas@twilight.mx

www.twilight.mx



/ [twightsadecv](https://www.facebook.com/twightsadecv)



/ [twightsadecv](https://twitter.com/twightsadecv)



/ [twightsadecv](https://www.youtube.com/twightsadecv)